

FLOS

09.3200.BZA Bronze

G-O White Light

Designed by Jorge Herrera, 2017



Semi recessed signalling lamp for indoor use on ceiling/wall. Power supply not included. 1000 mm power cable included.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Wall recessed
Environments	Indoor dry location
LED type	Top LED
Lamp category	LED
Number of heads	1
Power (W)	1.2
Source flux (lm)	96
System flux (lm)	4

Physical

Colour	Bronze
Trim	No
Orientation	Fixed
Recessed depth (mm)	56
Net weight (kg)	0.2
IP internal	20
IP external	65



Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)


Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)




Ecodesign and Energy Labelling



Replaceable (LED only) light source by a professional

Schematic light drawing



Photometric

Lighting type	Indirect, Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
Beam angle C0-180 (°)	74
Beam angle C90-270 (°)	74
UGR _L	17

Electrical

Insulation class	III
Forward voltage (V)	24
LED current (mA)	25
Driver	Remote excluded
Dimmable	Yes
Dimming type	Non Dimmable, Dimmable DALI 1

Notes

Equipment for remote installation in an accessible place: it does not fit through the luminaire installation hole. For Dali installation, the non-dimmable kit and the Dali controller are needed.

Accessories & Power Supply



REQUIRED
Power supply

Electrical

60.9157

Electronic transformer with constant voltage (24V) for LED. 8W, 110/240V, 50/60H



REQUIRED
Power supply

Electrical

60.8703

Electronic transformer with constant voltage (24V) for LED. 100/240V. 25W



OPTIONAL
Accessory

08.8422.00

Prepared for recessing



OPTIONAL
Accessory

Electrical

60.8640

Control Unit 1-10V



OPTIONAL
Accessory

Electrical

60.9766

Control Unit DALI



OPTIONAL
Control interface

Electrical

60.9678A

LED module Dali/Push dimmable control unit for 12, 24 or 48Vdc